Docket No.: 0033-0897P

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A low noise block down converter, comprising:

a plurality of local oscillators each including a dielectric resonator and having an oscillation frequency different from each other;

an electromagnetic coupling preventing member preventing electromagnetic coupling between one and another one of said dielectric resonators; and

a metal shielding box including one shielding chamber accommodating said plurality of local oscillators and said electromagnetic coupling preventing member,

wherein

said metal shielding box includes only one shielding chamber accommodating said plurality of local oscillators and

an electromagnetic coupling preventing member preventing electromagnetic coupling between one and another one of said dielectric resonators;

said electromagnetic coupling preventing member extending between any two of said dielectric resonators and receiving a reference potential.

- 2. (Original) The low noise block down converter according to claim 1, wherein said electromagnetic coupling preventing member includes a conductive bar having one end extending between any two of said dielectric resonators and receiving a reference potential.
- 3. (Original) The low noise block down converter according to claim 1, further comprising a substrate having a surface on which said plurality of local oscillators are mounted, wherein

Application No. 10/642,494 Docket No.: 0033-0897P Amendment dated August 30, 2005

Reply to Office Action of June 2, 2005

said electromagnetic coupling preventing member includes a conductive pattern

formed on the surface of said substrate between any two of said dielectric resonators and

receiving a reference potential.

4. (Original) The low noise block down converter according to claim 1, wherein

said electromagnetic coupling preventing member includes a metal plate provided between any

two of said dielectric resonators and receiving a reference potential.